




## N-Channel Enhancement Mode Field Effect Transistor



SOT-23-6L

## Product Summary

|                                     |               |
|-------------------------------------|---------------|
| • $V_{DS}$                          | 60V           |
| • $I_D$                             | 2.6A          |
| • $R_{DS(ON)}$ ( at $V_{GS}=10V$ )  | $<94m\Omega$  |
| • $R_{DS(ON)}$ ( at $V_{GS}=4.5V$ ) | $<132m\Omega$ |
| • ESD Level(HBM)                    | Class 1B      |

## General Description

- High density cell design for low  $R_{DS(ON)}$
- High Speed switching
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free
- Part no. with suffix "Q" means AEC-Q101 qualified

## Applications

- PWM applications
- Power management
- Load switch

## Limiting Values

| Parameter                              | Conditions                                |                                            | Symbol                           | Min | Max  | Unit |
|----------------------------------------|-------------------------------------------|--------------------------------------------|----------------------------------|-----|------|------|
| Drain-source Voltage                   |                                           |                                            | V <sub>DS</sub>                  | -   | 60   | V    |
| Gate-source Voltage                    |                                           |                                            | V <sub>GS</sub>                  | -20 | 20   |      |
| Continuous Drain Current (Note 1,2)    | Steady-State                              | T <sub>A</sub> =25°C,V <sub>GS</sub> =10V  | I <sub>D</sub>                   | -   | 2.6  | A    |
|                                        |                                           | T <sub>A</sub> =100°C,V <sub>GS</sub> =10V |                                  | -   | 1.6  |      |
| Pulsed Drain Current                   | T <sub>A</sub> =25°C,t <sub>p</sub> ≤10μs |                                            | I <sub>DM</sub>                  | -   | 19   |      |
| Maximum Body-Diode Continuous Current  | T <sub>A</sub> =25°C                      |                                            | I <sub>S</sub>                   |     | 1.4  |      |
| Total Power Dissipation (Note 1,2)     | Steady-State                              | T <sub>A</sub> =25°C                       | P <sub>D</sub>                   | -   | 1.3  | W    |
|                                        |                                           | T <sub>A</sub> =100°C                      |                                  | -   | 0.53 |      |
| Junction and Storage Temperature Range |                                           |                                            | T <sub>J</sub> ,T <sub>STG</sub> | -55 | 150  | °C   |

## Thermal Resistance

| Parameter                                       |              | Symbol          | Typ | Max | Units         |
|-------------------------------------------------|--------------|-----------------|-----|-----|---------------|
| Thermal Resistance Junction-to-Ambient (Note 2) | Steady-State | $R_{\theta JA}$ | -   | 94  | $^{\circ}C/W$ |

## Ordering Information (Example)

| PREFERRED P/N | PACKING CODE | Marking | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---------------|--------------|---------|----------------------|-------------------------|----------------------------|---------------|
| YJJ094N06AJKQ | F2           | 094N06  | 3000                 | 30000                   | 120000                     | 7" reel       |



# YJJ094N06AJKQ

## ■ Electrical Characteristics

| Parameter                         | Symbol              | Conditions                                                                                                | Min | Typ  | Max | Units |
|-----------------------------------|---------------------|-----------------------------------------------------------------------------------------------------------|-----|------|-----|-------|
| Static Parameter                  |                     |                                                                                                           |     |      |     |       |
| Drain-Source Breakdown Voltage    | BV <sub>DSS</sub>   | V <sub>GS</sub> =0V, I <sub>D</sub> =250μA, T <sub>J</sub> =25℃                                           | 60  | -    | -   | V     |
| Zero Gate Voltage Drain Current   | I <sub>DSS</sub>    | V <sub>DS</sub> =60V, V <sub>GS</sub> =0V, T <sub>J</sub> =25℃                                            | -   | -    | 1   | μA    |
|                                   |                     | V <sub>DS</sub> =60V, V <sub>GS</sub> =0V, T <sub>J</sub> =150℃                                           | -   | -    | 100 |       |
| Gate-Source Leakage Current       | I <sub>GSS</sub>    | V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V, T <sub>J</sub> =25℃                                           | -   | -    | ±10 | μA    |
| Gate Threshold Voltage            | V <sub>GS(th)</sub> | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA, T <sub>J</sub> =25℃                             | 1.1 | 1.6  | 2.1 | V     |
| Static Drain-Source On-Resistance | R <sub>DS(ON)</sub> | V <sub>GS</sub> =10V, I <sub>D</sub> =2A, T <sub>J</sub> =25℃                                             | -   | 79   | 94  | mΩ    |
|                                   |                     | V <sub>GS</sub> =4.5V, I <sub>D</sub> =1A, T <sub>J</sub> =25℃                                            | -   | 88   | 132 | mΩ    |
| Diode Forward Voltage             | V <sub>SD</sub>     | I <sub>S</sub> =1.4A, V <sub>GS</sub> =0V, T <sub>J</sub> =25℃                                            | -   | 0.78 | 1.2 | V     |
| Gate Resistance                   | R <sub>G</sub>      | f=1MHz, T <sub>J</sub> =25℃                                                                               | -   | 6.3  | -   | Ω     |
| Dynamic Parameters                |                     |                                                                                                           |     |      |     |       |
| Input Capacitance                 | C <sub>iss</sub>    | V <sub>DS</sub> =30V, V <sub>GS</sub> =0V, f=1MHz, T <sub>J</sub> =25℃                                    | -   | 322  | -   | pF    |
| Output Capacitance                | C <sub>oss</sub>    |                                                                                                           | -   | 21   | -   |       |
| Reverse Transfer Capacitance      | C <sub>rss</sub>    |                                                                                                           | -   | 16   | -   |       |
| Switching Parameters              |                     |                                                                                                           |     |      |     |       |
| Total Gate Charge                 | Q <sub>g</sub>      | V <sub>GS</sub> =10V, V <sub>DS</sub> =30V, I <sub>D</sub> =2A, T <sub>J</sub> =25℃                       | -   | 6.7  | -   | nC    |
| Gate-Source Charge                | Q <sub>gs</sub>     |                                                                                                           | -   | 0.64 | -   |       |
| Gate-Drain Charge                 | Q <sub>gd</sub>     |                                                                                                           | -   | 1.2  | -   |       |
| Reverse Recovery Charge           | Q <sub>rr</sub>     | I <sub>F</sub> =2A, di/dt=100A/μs, V <sub>GS</sub> =0V, V <sub>R</sub> =30V, T <sub>J</sub> =25℃          | -   | 7    | -   | nC    |
| Reverse Recovery Time             | t <sub>rr</sub>     |                                                                                                           | -   | 12   | -   | ns    |
| Turn-on Delay Time                | t <sub>D(on)</sub>  | V <sub>GS</sub> =10V, V <sub>DS</sub> =30V, I <sub>D</sub> =2A, R <sub>GEN</sub> =3Ω, T <sub>J</sub> =25℃ | -   | 4.6  | -   | ns    |
| Turn-on Rise Time                 | t <sub>r</sub>      |                                                                                                           | -   | 2.6  | -   |       |
| Turn-off Delay Time               | t <sub>D(off)</sub> |                                                                                                           | -   | 14.3 | -   |       |
| Turn-off Fall Time                | t <sub>f</sub>      |                                                                                                           | -   | 2.9  | -   |       |

### Note:

- The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
- The value of  $R_{\theta JA}$  is measured with the device mounted on the 40mm\*40mm\*1.1mm single layer FR-4 PCB board with 1 in<sup>2</sup> pad of 2oz. Copper, in the still air environment with  $T_A=25^\circ C$ . The maximum allowed junction temperature of 150 $^\circ C$ . The value in any given application depends on the user's specific board design.



## ■ Typical Electrical and Thermal Characteristics Diagrams




Figure 1. Output Characteristics; typical values




Figure 2. Transfer Characteristics; typical values




Figure 3. Capacitance Characteristics; typical values




Figure 4. Gate Charge; typical values




Figure 5. On-Resistance vs. Gate to Source Voltage; typical values




Figure 6. Normalized On-Resistance




Figure 7. RDS(on) vs. Drain Current; typical values




Figure 8. Forward characteristics of reverse diode; typical values




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation




Figure 13. Maximum Transient Thermal Impedance




Figure 14. Safe Operation Area

## ■ Test Circuits & Waveforms




Figure A. Unclamped Inductive Switching (UIS) Test Circuit & Waveform




Figure B. Gate Charge Test Circuit & Waveform




Figure C. Resistive Switching Test Circuit & Waveform





Figure D. Diode Recovery Test Circuit & Waveform

## ■ SOT-23-6L Package information




| SYMBOL   | DIMENSIONS |       |            |       |
|----------|------------|-------|------------|-------|
|          | INCHES     |       | Millimeter |       |
|          | MIN.       | MAX.  | MIN.       | MAX.  |
| A        | 0.012      | 0.020 | 0.300      | 0.500 |
| B        | 0.059      | 0.067 | 1.500      | 1.700 |
| C        | 0.104      | 0.116 | 2.650      | 2.950 |
| D        | 0.037BSC   |       | 0.950BSC   |       |
| G        | 0.075BSC   |       | 1.900BSC   |       |
| H        | 0.111      | 0.119 | 2.820      | 3.020 |
| J        | 0.000      | 0.004 | 0.000      | 0.100 |
| K        | 0.041      | 0.045 | 1.050      | 1.150 |
| L        | 0.012      | 0.024 | 0.300      | 0.600 |
| M        | 0.004      | 0.008 | 0.100      | 0.200 |
| $\theta$ | 0°         | 8°    | 0°         | 8°    |

### Note:

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05$ mm.
3. The pad layout is for reference purposes only.

## ■ Marking Information



### Note:

1. All marking is at middle of the product body
2. All marking is in laser printing
3. 094N06 is marking code
4. Body color: Black



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com> , or consult your nearest Yangjie's sales office for further assistance.