


Zener Diodes



Features

- Moisture sensitivity level 1
- Zener voltage 24V

Application

- Linear voltage regulator
- DC regulator
- Small-signal surge protection

Mechanical data

- **Package:** SOD-123
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Parameter	Symbol	Unit	Value
Forward voltage @ $I_F=10\text{mA}$	V_F	V	0.9
Power dissipation	P_D	mW	500
Maximum regulator current	I_{ZM}	mA	P_D / V_Z
Junction temperature	T_J	$^{\circ}\text{C}$	-55 to +150
Storage temperature	T_{STG}	$^{\circ}\text{C}$	-55 to +150



BZT52A24

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Type number	Device marking	V _z @ I _{zT} (V)			Z _{zT} (Ω)		Z _{zK} (Ω)		I _R (μA) @V _R		Typical temperature coefficient @ I _{zTC} mV/°C		Test Current I _{zTC}
		min.	typ.	max.	I _{zT} (mA)	max.	I _{zK} (mA)	max.	max	V _R (V)	Min	Max	mA
BZT52A24	GJ	23.76	24	24.24	5	65	1.0	235	0.045	16.8	18.4	23	5

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	250
Thermal resistance, junction-to-case	R _{θJ-C} ⁽¹⁾	°C/W	200

Note:

(1) Thermal resistance from junction to ambient and from junction to case mounted on P.C.B. with 8mm*9mm copper pad areas



■ Characteristics

Fig 1: P_D - T_a Curve




Fig 2: Zener Breakdown Characteristics





Fig 3: Typical Temperature Coefficient






BZT52A24

■ Ordering Information

Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
BZT52A24	F2	Approximate 0.011	3000	30000	120000	7" reel
BZT52A24	F3	Approximate 0.011	10000	/	210000	13" reel


■ Outline Dimensions



TOP VIEW




SIDE VIEW



SIDE VIEW

DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MM	MAX
A	0.140	0.152	3.550	3.850
B	0.100	0.112	2.550	2.850
C	0.055	0.071	1.400	1.800
D	0.037	0.053	0.950	1.350
E	0.020	0.028	0.510	0.710
G	0.006	0.018	0.150	0.450
H	0.003	0.010	0.080	0.250
J	0.000	0.006	0.000	0.150
θ	0	8°	0	8°

■ Suggested Pad Layout



UNIT: mm



BZT52A24

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.