

LOW VF Bridge Rectifiers




Features

- UL recognition, file #E230084
- Glass passivated chip junction
- Low VF
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.



Mechanical Data

- **Package:** 4KBJ
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■ Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	KBJL1508
Device marking code			KBJL1508
Maximum Repetitive Peak Reverse Voltage	VRRM	V	800
Maximum RMS Voltage	VRMS	V	560
Maximum DC blocking Voltage	VDC	V	800
Average Rectified Output Current @60Hz sine wave, R-load	With heatsink Tc = 105°C Without heatsink Ta = 25°C	IO A	15 3.2
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Tj=25°C	IFSM	A	250
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25°C			500
Current squared time @1ms≤t≤8.3ms Tj=25°C, rating of per diode	I ² t	A ² S	259
Storage temperature	Tstg	°C	-55 ~ +150
Junction temperature	Tj	°C	-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute	Vdis	KV	2
Mounting torque @Recommend torque: 5kg·cm	Tor	kg·cm	8

■ Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	KBJL1508
Maximum instantaneous forward voltage drop per diode	VF	V	IFM=7.5A	0.92
Maximum DC reverse current at rated DC blocking voltage per diode	IR	μA	Tj=25°C	5
			Tj=125°C	100
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	88

■ Thermal Characteristics ($T_a=25^\circ\text{C}$ Unless otherwise specified)





PARAMETER		SYMBOL	UNIT	KBJL1508	
Thermal Resistance	Between junction and ambient, Without heatsink	$R_{\theta JA}$	$^\circ\text{C}/\text{W}$	20	
	Between junction and case, With heatsink	$R_{\theta JC}$		1.5	

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

■ Ordering Information (Example)


PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
KBJL1508	B1	Approximate 4.27	20	1000	2000	Tube

■ Characteristics(Typical)





■ Outline Dimensions



4KBJ		
Dim	Min	Max
A	24.7	25.3
B	1.05	1.45
C	1.7	2.1
D	0.9	1.1
E	7.3	7.7
F	14.7	15.3
G	3.8	4.2
H	3.3	3.7
I	3.1	3.4
J	4.4	4.8
K	3.4	3.8
L	3.2	3.4
M	0.6	0.8
N	17.0	18.0
O	9.5	10.1



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com> , or consult your nearest Yangjie's sales office for further assistance.