## 保质期说明函

## 尊敬的客户:

根据以往客户的要求,YJ 设定标准的有效期为24个月,以产品包装上标注的日期开始计算。从以往数据看,我们对从包装上标注日期超过24个月的产品进行了重新测试,以验证材料仍然可以接受原始规格书的电气参数和性能要求。多年来,我们对数干批产品进行的复测结果表明,电气和性能均未出现退化。

对于超过 24 个月的产品,主要关注的是可焊性,而可焊性还与存储环境有关,故 YJ 建议客户对超过 24 个月的产品需进行可焊性测试。另外,针对我司所有产品 的储存环境建议如下:

- 1、 温度: 10-30℃、湿度: 10%-70%;
- 2、 无腐蚀性气体
- 3、 避免温度发生重大变化; 避免阳光直射;

特此说明!



邮箱: yiteng.wang@21yangjie.com

## **Expiration Policy**

## Dear customer:

Based on previous customer requests, YJ sets a standard expiration of 24 months, starting from the date indicated on the product packaging. Based on past data, we retested products that were more than 24 months from the date marked on the packaging to verify that the material could still accept the electrical parameters and functional requirements of the original datasheet. Over the years, we have retested thousands of lots of products and found no degradation in electrical and functional.

For products over 24 months old, the main concern is solder-ability, which is also related to the storage environment. Therefore, YJ recommends that customers conduct solder-ability tests on products over 24 months old. Also, the storage environment recommendations for all of our products are as follows:

- 4、 Temperature: 10-30 °C, humidity: 10%RH-70%RH;
- 5. No corrosive gas
- 6. Avoid significant changes in temperature; Avoid direct sunlight; Please note this!

Yangzhou Yangjie Electronig Technology Co.,Ltd. Quality Director: Chris Wang

Tel: 15152728806

Email: yiteng.wang@21yangjie.com